



## PRODUCT DESCRIPTION & BENEFITS

OXYTREAT 210 is a highly concentrated blend of catalyzed sodium sulfite, bisulfite, and organic inhibitors, designed as an oxygen scavenger and corrosion inhibitor for steam boiler systems and hydro testing applications. It offers rapid oxygen scavenging, effective corrosion protection for boilers, feed, simple monitoring procedures, and the convenience of direct dosing from the drum.

## TREATMENT AND DOSAGE REQUIREMENTS

OXYTREAT 210 is normally dosed so as to scavenge the oxygen in the water and to obtain a measurable reserve. The optimum treatment level depends on water temperature and the actual dosage rate will be determined by BCI sales Engineer.

OXYTREAT 210 may be either shot dosed or injected using a plastic dosage pump and delivery lines in undiluted form. OXYTREAT 210 will absorb oxygen from the atmosphere and therefore care should be taken in the application.

	Units	BCI Specifications	Test Methods
Appearance	-	Pale yellow liquid	ASTM-E2680
Density	g/ml	1.250 - 1.350	ASTM-D891
PH as supplied	-	5.00 - 6.00	ASTM-D1293

All technical data stated in this TDS are based on our actual laboratory analysis.

## ECOLOGY, HEALTH & SAFETY

For more information on the safe handling, storage, and disposal of chemical products, please refer to the most recent Safety Data Sheet (SDS).

## APPLICATIONS

OXYTREAT 210 is used as corrosion inhibitor for steam boiler systems. Consult your BCI sales Engineer for specific recommendations.

## AVAILABLE PACKAGING

- 30 L Jerrycan

## STORAGE CONDITIONS

OXYTREAT 210 could be stored for 12 months from the date of production if stored properly in undamaged, unopened, and original sealed packaging.

## DISCLAIMER

All sales by BCI, its subsidiaries, or affiliates "seller", are governed by the seller's standard terms and conditions of sale, available upon request unless otherwise agreed in writing. While information and recommendations regarding product application and end use are provided in good faith based on current knowledge and experience, the seller makes no warranty, express or implied, regarding merchantability, fitness for a particular purpose, or liability arising from use. Customers must evaluate the suitability of the product for their intended application, ensure compliance with third-party proprietary rights, and refer to the most recent product Datasheet, available on our site or upon request, for accurate guidance.

Version03: 01-01-2025

الصناعات الكيمائية الأساسية  
BASIC CHEMICAL INDUSTRIES

### HEAD OFFICE

P.O Box 1053, Dammam 31431, Saudi Arabia  
T: +966 13 821 7777 F: +966 13 847 26 48  
Email: Sales@bci.sa



### الفرع الرئيسي

ص ب ١٠٥٣، الدمام ٣١٤٣١، المملكة العربية السعودية  
ت: +٩٦٦ ١٣ ٨٢١ ٧٧٧٧ ف: +٩٦٦ ١٣ ٨٤٧ ٢٦٤٨  
البريد الإلكتروني: Sales@bci.sa